



U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

Note: Blank spaces are not permitted. If any item is not applicable, or no
 information is available, the space must be marked to indicate that.

IDENTITY (As Used on Label and List)
ROCKITE CEMENT

Section I

Manufacturer's Name
HARTLINE PRODUCTS CO., INC.
 Address (Number, Street, City, State, and ZIP Code)
4568 MAYFIELD RD., SUITE 202
CLEVELAND, OHIO 44121

Emergency Telephone Number
(216) 291-2303
 Telephone Number for Information
(216) 291-2303
 Date Prepared
5-15-06
 Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identify Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	CAS NO.
Gypsum (calcium sulfate) % WT: 98	15 mg/m ³ Total Dust 5 mg/m ³ Respirable Dust	10 mg/m ³ Total Dust	7778-18-9
Portland Cement % WT: 2	10 mg/m ³ Total Dust 5 mg/m ³ Respirable Dust	10 mg/m ³ Total Dust	65997-15-1

Section III — Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	2.7
Vapor Pressure (mm Hg.)	NA	Melting Point (decomposes)	1450°C
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA

Solubility in Water: 0.2% Hardening Time: 12-15 Minutes

Appearance and Odor
 White, Off-White, Gray or pigmented powder. - Low odor.

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	None	Flammable Limits	LEL NA	UEL NA
Extinguishing Media	Not Combustible			
Special Fire Fighting Procedures	None			

Unusual Fire and Explosion Hazards
 None

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts Above 1450°C - SO₂ and CaO

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Yes

Health Hazards (Acute and Chronic) Acute: Eyes - May cause irritation. Skin - May develop sufficient heat to cause burns if a large mass, such as a cast of an arm or leg, is kept in contact with skin while hardening. Inhalation: Dust is considered a nuisance dust. Chronic: None

Carcinogenicity: Not carcinogenic. NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure

Medical Conditions Generally Aggravated by Exposure EYES: Flood eyes for 15 minutes with water. SKIN: Remove from skin by washing. If irritation continues, see physician. Gypsum cement hardens when wetted and if ingested, may result in obstruction. See physician.

Emergency and First Aid Procedures

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Sweep up. Avoid creating excessive dust. Slurry may plug drains.

Waste Disposal Method In accordance with local, state and federal regulations.

Precautions to Be Taken in Handling and Storing Dew point conditions or other conditions causing presence of liquid water during storage will harden gypsum cement.

Other Precautions

Section VIII - Control Measures

Respiratory Protection (Specify Type) NIOSH approved nuisance dust respirator if above TLV.

Ventilation	Local Exhaust	If above, TLV	Special
	Mechanical (General)		Other

Protective Gloves If dust or slurry is irritating. Eye Protection Dust goggles or safety glasses if dust is annoying.

Other Protective Clothing or Equipment None

Work/Hygienic Practices