

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 04/11/2007

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1 Prot. Equipm.:

NFPA

Flammability: 1 Reactivity: 0 Health: 1 Special Haz.:

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 30 %
Methyltriacetoxysilane	4253-34-3	1 - 5 %
<u>B. NON-HAZARDOUS</u>		
Dimethylpolysiloxane	70131-67-8	60 - 90 %
Treated Filler	68611-44-9	5 - 10 %

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! May be harmful if swallowed, inhaled or absorbed through skin. Irritating to eyes, respiratory system and skin. May cause central nervous system depression.

Form: solid Color: translucent Odor: Acetic acid

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

SKIN

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product. May be absorbed through skin and produce effects as listed under "Ingestion".

INHALATION

Causes mild respiratory tract irritation. Applies in uncured state. May be harmful if inhaled.

EYES

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

Pre-existing skin or respiratory diseases.

SUBCHRONIC (TARGET ORGAN)

Skin; Central nervous system

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Eyes; Inhalation

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. Get medical attention if irritation persists.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

METHOD: Not applicable
IGNITION TEMPERATURE: Unknown
FLAMMABLE LIMITS IN AIR - LOWER (%): Not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE
Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA
All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

STORAGE
Store away from heat, sources of ignition, and incompatibles. Keep out of the reach of children.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container closed when not in use. Avoid contact with skin and eyes. Use only in well-ventilated areas. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Product releases acetic acid during application and curing. Attention: Not for injection into humans.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS
Eyewash stations; Showers; Use only in well-ventilated areas.

RESPIRATORY PROTECTION
If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES

Rubber gloves

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	Not applicable
VAPOR PRESSURE (20 C) (MM HG):	Not applicable
VAPOR DENSITY (AIR=1):	Not applicable
FREEZING POINT:	Not applicable
MELTING POINT:	Not applicable
PHYSICAL STATE:	solid
ODOR:	Acetic acid
COLOR:	translucent
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY (WATER=1):	ca. 1.04
DENSITY:	ca. 1.04 g/cm ³
ACID / ALKALINITY (MEQ/G):	Not applicable
pH:	Not applicable
VOLATILE ORGANIC CONTENT (VOL):	Not applicable
SOLUBILITY IN WATER (20 C):	Insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Toluene
VOC EXCL. H₂O & EXEMPTS (G/L):	36

GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); Carbon monoxide; Silicon dioxide.; formaldehyde; Acetic acid; This product contains components which can generate formaldehyde at approximately 300 F (150 C) and above in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. An MSDS for formaldehyde is available from Momentive Performance Materials, Inc.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

None.

SENSITIZATION

No data available

SKIN IRRITATION

No data available

EYE IRRITATION

No data available

MUTAGENICITY

Unknown

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY

Ecotoxicological data for this product is not available.

CHEMICAL FATE

No data available

DISTRIBUTION

No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Japan Inventory of Existing & New Chemical Substances (ENCS)	y (Positive listing)
Korea Existing Chemicals Inventory (KECI)	y (Positive listing)
China Inventory of Existing Chemical Substances	y (Positive listing)
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)
TSCA list	y (Positive listing)
EU list of existing chemical substances	y (Positive listing)
Canada NDSL Inventory	n (Negative listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	n (Negative listing)
Canada DSL Inventory	q (quantity restricted)

For inventories that are marked as quantity restricted or special cases, please contact GE.

**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

US Regulatory Information

CERCLA

PRODUCT COMPOSITION

Chemical

CERCLA Reportable Quantity

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS: 3214.10 Mastic Based on Rubber

ECCN: EAR99

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm =



**GE012A 12C-Crtrg (0.730 Lbs-0.331 Kg)
Silicone Construction Sealant**

parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status
not required under 40 CFR part 720.30(h-2).