

GreenGuard® SILL SEALER® DATA SHEET



Description: GreenGuard® Sill Sealer® is a corrugated polyethylene foam gasket material used to prevent air leakage between the foundation wall and the sill plate and also around window and door frames.

Product Sizes:

Product Number	Dimensions	Rolls/Bag	Lineal Feet/Bag	Bags/Pallet	Rolls/Pallet	Lineal Feet/Pallet
AS5035	1/4" x 3 1/2" x 50'	6	300	18	108	5400
AS5055	1/4" x 5 1/2" x 50'	4	200	18	72	3600
AS5075	1/4" x 7 1/2" x 50'	3	150	18	54	2700

Pallet Sizes (L,W,H): AS5035 = 42.31", 42.31", 47.25"
AS5055 = 42.31", 42.31", 49.25"
AS5075 = 42.31", 42.31", 50.25"

Typical Physical Properties

<u>Property</u>	<u>Test Method</u>	<u>GreenGuard® Sill Sealer</u>
Color	Pantone	Green (344U)
Thickness (inches)	ASTM D 1777	0.25
Weight (g/100 in ²)	ASTM D 3776	23.80
Distortion Temperature (°F)		220
Maximum Recommended Use Temperature (°F)		165
Water Vapor Transmission Rate (perm)	ASTM E 96 Procedure A	0.3

WARNING: Foam plastic insulation will ignite if exposed to fire of sufficient heat and intensity. Protect foam insulation from exposure to open flame or other ignition sources during shipment, storage, and installation.

Pactiv Building Products believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Pactiv does not guarantee results from use of such products or other information herein and disclaims all liability from any damage or loss. NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN AS TO THE MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR OTHERWISE WITH RESPECT TO THE PRODUCTS REFERRED TO.

DS-SILL
3/04