

**Material Safety Data Sheet For
ATL004, ATL016, ATL032, ATL128, ATL55**

Coilhose Pneumatics Inc.
19 Kimberly Road
East Brunswick, NJ 08816
Phone: 732-390-8480

REVISION DATE
21-OCT-05

DATE ISSUED
30-NOV-05

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME:
Air Tool Lubricant

PRODUCT #:
ATL004, ATL016, ATL032, ATL128

CHEMICAL NAME:
N/A – Mixture

CAS #'S:
Mixture

PRODUCT APPEARANCE AND ODOR:
Amber liquid, petroleum odor

CHEMICAL FAMILY:
Petroleum hydrocarbon

SYNONYMS:
Petroleum-based hydraulic oil

EMERGENCY TELEPHONE:
1-908-862-9300 / 800-764-7661 Poison Control

COMPONENTS AND HAZARD INFORMATION

COMPONENTS:	W/W	HAZARD DATA (TLV, LD50, LC50, ETC.):
Petroleum-based lubricating oil CAS #'s: 64742-54-7, 64742-65-0	> 99%	5 mg/m3 ACGIH/OSHA TWA (as an oil mist)
Butylated hydroxytoluene CAS #'s: 128-39-2	< 1%	N/E

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):

Health	Flammability	Reactivity
1	1	0

TRANSPORTATION INFORMATION

TRANSPORTATION INCIDENT INFORMATION:
DOT: Not regulated.

EMERGENCY FIRST AID

EYE CONTACT: If splashed into the eyes, flush with clear water 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT: In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

INHALATION: Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

INGESTION: If ingested, do not induce vomiting. Call a physician immediately.

FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT (MINIMUM):
365°F Test method: COC

AUTOIGNITION TEMPERATURE:
N/E

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) – HAZARD IDENTIFICATION

Health	Flammability	Reactivity
1	1	0

FLAMMABLE OR EXPLOSIVE LIMITS (approximate percent by volume in air):
Estimated values: lower: N/E upper: N/E

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES:

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type product, depending on size or potential size of fire and circumstances related to the situation. Water froth may be used to flush spills away from exposure. Minimize breathing gases, vapor, fumes, and smoke, or decomposition products. Use supplied air-breathing equipment for enclosed or confined spaces or as otherwise needed.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

n/a

"EMPTY" CONTAINER WARNING:

Empty containers retain residue (liquid or vapor) and can be dangerous. DO NOT PRESSURIZE, WELD, CUT, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged, and returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with government regulations.

HEALTH AND HAZARD INFORMATION

EXPOSURE LIMIT FOR TOTAL PRODUCT:

Monitor data listed in COMPONENTS and HAZARD INFORMATION section.

VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human and health risks, which vary from person to person. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure):

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis. Product contacting the eye may cause irritation. Product has a low order of oral and dermal toxicity. Possible aspiration hazard. Induced vomiting may cause aspiration of product into the lungs. (See Emergency First Aid Section).

PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes.

BOILING RANGE:
Wide range

VAPOR PRESSURE:
< 0.1 @ 38°C/100°F

PHYSICAL DATA (Continued)

SPECIFIC GRAVITY (25°C/25°C): (WATER = 1) <1.0	VAPOR DENSITY (AIR = 1): >8
MOLECULAR WEIGHT: Wide Range	VAPOR PRESSURE: < 0.1 mmHg @ 20°C
EVAPORATION RATE @ 1 ATM. AND 25°C (77°F) (n-BUTYL ACETATE = 1): Not available	SOLUBILITY IN WATER @ 1 ATM. AND 25°C (77°F): Negligible
BOILING RANGE: Not available	VOC Content: 0.11 LB/GAL

REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite, etc., as this represents a serious explosion hazard.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide, oxides of sulfur, and other decomposition products, in case of incomplete combustion.

CONDITIONS TO AVOID:

Open Flames.

TOXICITY

ORAL (Acute)	N/E
DERMAL (Acute)	N/E
EYE	N/E
INHALATION (Acute)	N/E
CHRONIC, SUBCHRONIC, ETC.	N/E
Medical Conditions Aggravated by Exposure:	Unknown

This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA.

SARA Section 313 Status:

This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHODS:

(Consult federal, state, or local authorities for proper disposal procedures.) Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTIONS AND PRECAUTIONS

VENTILATION:

(Always maintain below permissible exposure limits.) Use local exhaust to capture vapor, mist or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations or vapor in air.

RESPIRATORY PROTECTION:

(Use only NIOSH approved equipment.) Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or vapor respirator type under misting conditions. Use can or cartridge, gas or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERED CONTROLS:

Keep containers closed when not in use. Do not handle near heat, sparks, flame, or strong oxidants.

PERSONAL HYGIENE:

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners, followed by washing thoroughly with soap and water.

PREPARED BY: Luke McHale, Regulatory Manager

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.