

MATERIAL SAFETY DATA SHEET: ELECTRA COAT AEROSOL**Section I - General Information**

(000000-000000- - 5687)

Date of Issue:
8/20/2004 12:00:00 AM**Supercedes:**
7/28/2000 12:00:00 AM**Chemical Name & Synonyms:**
N/A**Trade Name & Synonyms:**
ELECTRA COAT AEROSOL**Chemical Family:**
ALIPHATIC/AROMATIC HYDROCARBON BLEND**Formula is a mixture:** [✓]**Manufacturer Name:**
CERTIFIED LABS, DIV. OF NCH CORP.**Manufacturer Address:**
BOX 152170
IRVING, TEXAS 75015**Prepared By:**
M McDowell/Chemist**Product Code Number:**
5687**Emergency Phone Number:**
800-424-9300**Section II - Hazardous Ingredients**

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Chemical Name (Ingredients)	Hazard	TLV	PEL	STEL	CAS #
XYLENE	IRR/FLAM	100 PPM 1	100 PPM 2	N/E	1330-20-7
STYRENE POLYMER WITH 1,3 BUTADIENE	IRRITANT	N/E 1	N/E 2	N/E	9003-55-8
N-HEXANE	IRR/FLAM	50 PPM \$1	500 PPM 2	N/E	110-54-3
PROPANE	FLAM/ASPHY	1000 PPM*1	1000 PPM 2	N/E	74-98-6
BUTANE	FLAM/ASPHY	1000 PPM*1	N/E 2	N/E	106-97-8
ACETONE	IRR/FLAM	500 PPM 1	1000 PPM 2	750 PPM 1	67-64-1
TOLUENE	IRR/FLAM	50 PPM 1	200 PPM 2	300 PPM 2	108-88-3

\$ SKIN

* ALIPHATIC HYDROCARBON GASES

Section III - Physical Data

Boiling Point (°F): N/E	Specific Gravity (H₂O=1): 0.90
Vapor Pressure (mm Hg): <75 PSI	Color: COLORLESS-LT STRAW
Vapor Density (Air=1): >1	Odor: AROMATIC SOLVENT
pH @ 100% : N/A	Clarity: TRANSPARENT/HAZY
% Volatile by Volume: 88	Evaporation Rate (BuAc=1): <1
H₂O Solubility: NEGLIGIBLE	Viscosity: SEMI-VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point: -10°F	Method Used: SETAFLASH
Flammable Limits: PRODUCT MIXTURE	UEL: 12.8%
LEL: 0.9%	Aerosol Level (NFPA 30B): 3

Extinguishing Media:

Foam Alcohol Foam CO2
 Dry Chemical Water Spray Other

NFPA 704 Hazard Rating:

4-Extreme	Health: 2
3-High	Flammability: 4
2-Moderate	Instability: 0
1-Slight	Special:
0-Insignificant	

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO DISTANT AND/OR LOW-LYING SOURCES OF IGNITION AND FLASHBACK. PRODUCT MAY PRODUCE A FLOATING FIRE HAZARD AS LIQUID FLOATS ON WATER. FLAME EXTENSION: >30 INCHES. BURNBACK: 6 INCHES

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:**Acute: (Short Term Exposure)**

EYE CONTACT: CAUSES IRRITATION SEEN AS TEARING AND REDNESS. SKIN CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS. PRODUCT MAY BE ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEFATTING, AND CRACKING OF THE SKIN. INHALATION: MAY CAUSE RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. AT LOW VAPOR CONCENTRATIONS, NO HARMFUL EFFECTS ARE EXPECTED. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND MAY BE FATAL. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL.

Chronic: (Long Term Exposure)

CHRONIC INHALATION OF SOLVENTS LIKE XYLENE AND TOLUENE HAVE CAUSED HEARTBEAT IRREGULARITY, HEARTBEAT INCREASE, AND PERMANENT CENTRAL AND PERIPHERAL NERVOUS SYSTEM DAMAGE, RESULTING IN DECREASED LEARNING ABILITY, LOSS OF MEMORY, PERSONALITY CHANGES, AND DISTURBANCES IN GAIT. A CONDITION KNOWN AS "PAINTER'S SYNDROME" CAN OCCUR CAUSING A LOSS OF SENSATION IN THE ARMS AND HANDS (PERIPHERAL NEUROPATHY). PROLONGED OR REPEATED EXPOSURE MAY CAUSE CARDIAC SENSITIZATION. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. IN RARER CASES, AN INCREASED SENSITIVITY TO SUNLIGHT (PHOTOSENSITIVITY) MAY OCCUR. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS, PREEXISTING NEUROLOGICAL CONDITIONS, HEPATIC AND RENAL CONDITIONS, CARDIOVASCULAR, AND AUDITORY SYSTEM CONDITIONS. TARGET ORGANS: CENTRAL AND PERIPHERAL NERVOUS SYSTEMS, KIDNEYS, LIVER, BLOOD, AND AUDITORY SYSTEM.

Primary Routes of Entry

Inhalation Ingestion Absorption

Emergency First Aid Procedures:**Inhalation:**

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

Eye Contact:

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Skin Contact:

WIPE AWAY MATERIAL WITH A CLOTH WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. CLEAN CLOTHING AND SHOES.

Ingestion:

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON.

Notes to Physician:

INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL. DEPENDING ON THE AMOUNT INGESTED AND RETAINED AS WELL AS THE TOXICITY OF THE PRODUCT, GASTRIC LAVAGE SHOULD BE CONSIDERED. KEEP PATIENT'S HEAD BELOW HIPS TO PREVENT PULMONARY ASPIRATION. IF COMATOSE, A CUFFED ENDOTRACHEAL TUBE WILL PREVENT ASPIRATION.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

IARC

NTP

OSHA

ACGIH

Other

VOC CONTENT: 88% BY WEIGHT, 792 G/L

MIR CONTENT: 1.47

XYLENE

ORL-RAT LD50: 4300 MG/KG 3.

IHL-RAT LC50: 5000 PPM/4H 3.

IHL-HMN LCLo: 1000 PPM/6H 3.

SKN-RBT LD50: >1700 MG/KG 3.

SKN-RBT SDT: 500 MG/24H MODERATE 3.

EYE-RBT SDT: 5 MG/24H SEVERE 3.

STYRENE POLYMER WITH 1,3 BUTADIENE

EYE-RBT SDT: 500 MG/24H MILD 3.

N-HEXANE

ORL-RAT LD50: 25 GM/KG 3.

IHL-HMN TCLo: 190 PPM/8W 3.

EYE-RBT SDT: 10 MG MILD 3.

THIS MATERIAL MAY ADVERSELY AFFECT THE MALE REPRODUCTIVE SYSTEM BASED ON TESTING IN LABORATORY ANIMALS. 4.

PROPANE

NO TOXICOLOGICAL DATA ARE AVAILABLE

N-BUTANE

IHL-RAT LC50: 658 G/M3/4H 3.

IHL-MUS LC50: 680 G/M3/4H 3.

HUMAN VOLUNTEERS EXPOSED REPEATEDLY TO GASES OF SIMILAR HYDROCARON MIXTURES RANGING FROM 250 TO 1000 PPM EXHIBITED NO CARDIAC OR PULMONARY FUNCTION ABNORMALITIES. 4.

ACETONE

EYE-RBT SDT: 20 MG/ 24H MODERATE 3.

SKN-RBT SDT: 500 MG/24H MILD 3.

IHL-RAT LC50: 50100 MG/M3/8H 3.

ORL-RAT LD50: 5800 MG/KG 3.

TOLUENE

EYE-RBT SDT: 870 UG MILD 3.

SKN-RBT SDT: 20 MG/24H MODERATE 3.

SKN-RBT LD50: 12.2 G/KG 3.

ORL-HMN LDLo: 50 MG/KG 3.

ORL-RAT LD50: 636 MG/KG 3.

IHL-RAT LC50: 49 G/M3/4H 3.

ANIMAL STUDIES HAVE SHOWN THAT REPEATED INHALATION OF HIGH LEVELS PRODUCED HISTOLOGICAL CHANGES IN THE BRAIN, DEGENERATION OF THE HEART TISSUE, CARDIAC SENSITIZATION AND POSSIBLE IMMUNE SYSTEM SUPPRESSION. INTENTIONAL ABUSE OF TOLUENE VAPORS HAS BEEN LINKED TO DAMAGE OF THE BRAIN, KIDNEY, AND LIVER. 4.

MANY CASE STUDIES INVOLVING ABUSE DURING PREGNANCY INDICATE THAT TOLUENE CAN CAUSE BIRTH DEFECTS, GROWTH RETARDATION AND LEARNING DIFFICULTIES. 4.

Section VII - Reactivity Data

Stability [✓] Stable [] Unstable Conditions to Avoid: AVOID HEAT, HOT SURFACES, SPARKS, AND OPEN FLAMES.	Hazardous Polymerization [✓] Will not occur [] May occur Conditions to Avoid: N/A
---	--

Incompatibility (Materials to Avoid):
STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE.

Hazardous Decomposition Products:
OXIDES OF CARBON.

Section VIII - Spill Or Leak Procedures

Steps to be Taken if Material is Released or Spilled:
ELIMINATE IGNITION SOURCES OF ELECTRICAL, STATIC, OR FRICTIONAL SPARKS. DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, WEAR APPROPRIATE PROTECTIVE CLOTHING, VENTILATE THE AREA, ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. USE CARE AS SPILLS MAY BE SLIPPERY.

Waste Disposal Method(s):
DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. TYPICAL DISPOSAL IS TO WRAP THE EMPTY AEROSOL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN THE TRASH. AEROSOL RECYCLING PROGRAMS ARE AVAILABLE IN MANY AREAS. DO NOT PUNCTURE OR INCINERATE THIS CONTAINER.

Neutralizing Agent:
N/A

Section IX - Special Protection Information

Required Ventilation:
LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF MISTS OR VAPORS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:
RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSI Z88.2-1992.

Glove Protection:
NEOPRENE OR NITRILE RUBBER GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:
SAFETY GLASSES WITH SIDE SHIELDS IF THE METHOD OF USE PRESENTS THE LIKELIHOOD OF EYE CONTACT. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:
WEAR GENERAL-DUTY WORK CLOTHES AND SHOES. REMOVE SOAKED CLOTHING AND SHOES. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

Section X - Storage and Handling Information

Storage Temperature

Max: 120°F Min: 35°F

Storage Conditions

Indoors Outdoors Heated Refrigerated

Precautions to be Taken in Handling and Storing:

USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY, AND OPEN FLAME.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Section XI - Regulatory Information

Chemical Name	CAS Number	Upper % Limit
XYLENE	1330-20-7	35
HEXANE	110-54-3	25

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2004. 2. OSHA PEL. 3 REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFOWeb, 2004. 4. VENDOR'S MSDS. ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING. - IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE, COMB:COMBUSTIBLE, CORR:CORROSIVE CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED CUP, LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LIMIT, STEL:SHORT-TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE, MUT:MUTAGENIC, ASPHYX:ASPHYXIAN, PNOS:PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, SDT:STANDARD DRAIZE TEST, ORL:ORAL, IHL:INHALATION, HMN:HUMAN
THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2007 NCH Corporation All rights reserved.