

MATERIAL SAFETY DATA SHEET: FOAMING CUT THRU AEROSOL

Section I - General Information

{000000-000000- - 5439 }

Date of Issue:
11/22/2005 12:00:00 AM
Chemical Name & Synonyms:
N/A
Chemical Family:
TERPENE SOLUTION
Manufacturer Name:
CERTIFIED LABS, DIV. OF NCH CORP.
Manufacturer Address:
BOX 152170
IRVING, TEXAS 75015
Prepared By:
M McDowell/Chemist

Supercedes:
6/21/2002 12:00:00 AM
Trade Name & Synonyms:
FOAMING CUT THRU AEROSOL
Formula is a mixture: [✓]

Product Code Number: 5439 **Emergency Phone Number:** 800-424-9300

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

<u>Chemical Name (Ingredients)</u>	<u>Hazard</u>	<u>TLV</u>	<u>PEL</u>	<u>STEL</u>	<u>CAS #</u>
D-LIMONENE	IRRITANT	N/E 1	N/E 2	N/E	5989-27-5
HEXYLENE GLYCOL	IRR/SENS	N/E 1	N/E 2	25 PPM \$1	107-41-5
TALL OIL FATTY ACID	IRRITANT	5 MG/M3 #1	5 MG/M3 #2	10 MG/M3#1	61790-12-3
PROPANE	ASPHYX	1000 PPM*1	1000 PPM 2	N/E	74-98-6
ISOBUTANE	ASPHYX	1000 PPM*1	N/E 2	N/E	75-28-5

\$ CEILING LIMIT
OIL MIST VALUES
* ALIPHATIC PETROLEUM GASES

Section III - Physical Data

Boiling Point (°F): >212°	Specific Gravity (H₂O=1): 0.983
Vapor Pressure (mm Hg): 89.9	Color: BEIGE TO TAN
Vapor Density (Air=1): 1.7	Odor: CITRUS
pH @ 100%: 8.7	Clarity: OPAQUE
% Volatile by Volume: 97	Evaporation Rate (BuAc=1): 10.6
H₂O Solubility: EMULSIFIABLE	Viscosity: NON-VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point:>212°F **Method Used:**SETA-FLASH
Flammable Limits:PRODUCT MIXTURE **UEL:**9.5%
LEL:0.7% **Aerosol Level (NFPA 30B):**1

Extinguishing Media:

[✓] Foam	[✓] Alcohol Foam	[✓] CO2
[✓] Dry Chemical	[✓] Water Spray	[] Other

NFPA 704 Hazard Rating:

4-Extreme	Health: 2
3-High	Flammability: 1
2-Moderate	Instability: 0
1-Slight	Special:
0-Insignificant	

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. EXTINGUISHING MEDIA SHOULD BE CHOSEN BASED ON THE NATURE OF THE SURROUNDING FIRE. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

FLAME EXTENSION IS 0 INCHES, BURNBACK IS 0 INCHES.

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR PRODUCT MIXTURE. SEE SECTION II.

Effects of Overexposure:

Acute: (Short Term Exposure)

EYE CONTACT: CAUSES SEVERE IRRITATION SEEN AS STINGING, TEARING, SWELLING, REDNESS, EXCESSIVE BLINKING, BLURRED VISION, AND A BURNING SENSATION. CAUSES CORNEAL DAMAGE. SKIN CONTACT: CAUSES IRRITATION SEEN AS ITCHING, REDNESS, SWELLING, AND A BURNING SENSATION. MAY CAUSE ALLERGIC SKIN REACTION SEEN AS DELAYED SKIN RASH WHICH MAY BE FOLLOWED BY BLISTERING, SCALING, AND OTHER SKIN EFFECTS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEPATting, AND CRACKING OF THE SKIN. INHALATION: MAY CAUSE RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. MAY CAUSE ALLERGIC RESPIRATORY REACTION. AT LOW VAPOR CONCENTRATIONS, NO HARMFUL EFFECTS ARE EXPECTED. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND MAY BE FATAL. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SIMILAR TO INHALATION.

Chronic: (Long Term Exposure)

MAY CAUSE SKIN AND RESPIRATORY SENSITIZATION IN SOME INDIVIDUALS. ON RARE OCCASIONS. PROLONGED AND REPEATED EXPOSURE TO HYDROCARBON MIST POSES A RISK OF CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGHING ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO PULMONARY EDEMA AND HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATION AND HEART RATES AS WELL AS A BLuish DISCOLORATION OF THE SKIN. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. IN RARER CASES, AN INCREASED SENSITIVITY TO SUNLIGHT (PHOTOSENSITIVITY) MAY OCCUR. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS. TARGET ORGANS: BLOOD-FORMING ORGANS, LUNGS, AND CENTRAL NERVOUS SYSTEM. THE PRIMARY ROUTES OF EXPOSURE ARE SKIN AND EYE CONTACT.

Primary Routes of Entry

[✓] Inhalation	[] Ingestion	[✓] Absorption
----------------	---------------	----------------

Emergency First Aid Procedures:

MATERIAL SAFETY DATA SHEET: FOAMING CUT THRU AEROSOL

Inhalation:
REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

Eye Contact:
IMMEDIATELY RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HOLD THE EYELIDS APART TO ENSURE RINSING OF THE ENTIRE SURFACE OF THE EYES AND LIDS WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

Skin Contact:
WASH AFFECTED AREAS WITH LARGE AMOUNTS OF SOAP AND WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE.

Ingestion:
GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON.

Notes to Physician:
INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL. DEPENDING ON THE AMOUNT INGESTED AND RETAINED AS WELL AS THE TOXICITY OF THE PRODUCT, GASTRIC LAVAGE SHOULD BE CONSIDERED. KEEP PATIENT'S HEAD BELOW HIPS TO PREVENT PULMONARY ASPIRATION. IF COMATOSE, A CUFFED ENDOTRACHEAL TUBE WILL PREVENT ASPIRATION.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By: IARC NTP OSHA ACGIH Other

TOTAL VOC CONTENT: 20.7% BY WEIGHT, 26.5% BY VOLUME, 192 G/L
VOC CONTENT AFTER LVP EXEMPTION: 18.3% BY WEIGHT, 24.3% BY VOLUME, 170.5 G/L

D-LIMONENE
ORL-RAT LD50: 4400 MG/KG 4.
SKN-RBT LD50: >5 G/KG 3.
SKN-RBT: SEVERELY IRRITATING 3.
EYE-RBT: SEVERELY IRRITATING 3.

HYDROCARBON MISTS DERIVED FROM HIGHLY REFINED OILS ARE REPORTED TO HAVE LOW ACUTE AND SUB-ACUTE TOXICITIES IN ANIMALS. EFFECTS FROM SINGLE AND SHORT-TERM REPEATED EXPOSURES TO HIGH CONCENTRATIONS OF MINERAL OIL MISTS WELL ABOVE APPLICABLE WORKPLACE EXPOSURE LEVELS INCLUDE LUNG INFLAMMATORY REACTION, LIPOID GRANULOMA FORMATION, AND LIPOID PNEUMONIA. 3.

HEXYLENE GLYCOL
ORL-RAT LD50: 3700 MG/KG 4.
ORL-RAT LDLO: 33600 MG/KG/28D-1 CHANGES IN LIVER, BLADDER, KIDNEY 4.
IHL-RAT LC50: NO DEATHS: 66 PPM/8H 3.
SKN-RBT LD50: 8560 UL/KG 4.
SKN-RBT SDT: 465 MG/24H 4.
EYE-RBT SDT: 93 MG/24H SEVERE 4.

IN A REPEATED PATCH TEST STUDY OF ECZEMA PATIENTS, HEXYLENE GLYCOL ELICITED EDEMA AND ERYTHEMA IN 2.8% OF THE SUBJECTS TESTED (CONTACT DERMATITIS 21:154, 1989) 3.

HEXYLENE GLYCOL HAS PRODUCED EVIDENCE OF SLIGHT FETAL TOXICITY AT A MATERNALLY TOXIC DOSE (1000 MG/KG/DAY) 3.

TALL OIL FATTY ACID
ORL-RAT LD50: >10,000 MG/KG 3.
SKN-RBT LD50: >2000 MG/KG 3.
SKN: MILD IRRITATION, EFFECTS REVERSIBLE IN LESS THAN 72 HOURS 3.
EYE: MILD IRRITATION, EFFECTS REVERSIBLE IN LESS THAN 72 HOURS 3.

PROPANE
IHL-LC50 >40% BY VOLUME 3.

ISOBUTANE
IHL-RAT LC50: 57 PPH/15M 4.

Section VII - Reactivity Data

Stability <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable Conditions to Avoid: AVOID HEAT, HOT SURFACES, SPARKS, AND OPEN FLAMES.	Hazardous Polymerization <input checked="" type="checkbox"/> Will not occur <input type="checkbox"/> May occur Conditions to Avoid: N/A
---	--

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE; REDUCING AGENTS SUCH AS SODIUM THIOSULFATE, ACIDS AND BASES. STRONG ACIDS, CLAYS, ALUMINUM CHLORIDE, HALOGENS, IODINE PENTAFLUORIDE, VINYL CHLORIDE, SOME PLASTICS AND RUBBER.

Hazardous Decomposition Products:

OXIDES OF CARBON AND SULFUR.

Section VIII - Spill Or Leak Procedures

Steps to be Taken if Material is Released or Spilled:

DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, WEAR APPROPRIATE PROTECTIVE CLOTHING. VENTILATE THE AREA. ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. USE CARE AS SPILLS MAY BE SLIPPERY.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. TYPICAL DISPOSAL IS TO WRAP THE EMPTY AEROSOL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN THE TRASH. AEROSOL RECYCLING PROGRAMS ARE AVAILABLE IN MANY AREAS. DO NOT PUNCTURE OR INCINERATE THIS CONTAINER.

Neutralizing Agent:

N/A

Section IX - Special Protection Information

Required Ventilation:

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF MISTS OR VAPORS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR

MATERIAL SAFETY DATA SHEET: FOAMING CUT THRU AEROSOL

STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSI Z88.2-1992.

Glove Protection:

NEOPRENE OR NITRILE RUBBER GLOVES SHOULD BE WORN. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:

CHEMICAL GOGGLES SHOULD BE WORN WHEN HANDLING. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:

WEAR PROTECTIVE CLOTHING WHEN HANDLING. REMOVE SOAKED CLOTHING AND SHOES. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

Section X - Storage and Handling Information

Storage Temperature Max: 120°F Min: 40°F	Storage Conditions <input type="checkbox"/> Indoors <input type="checkbox"/> Outdoors <input type="checkbox"/> Heated <input type="checkbox"/> Refrigerated
---	---

Precautions to be Taken in Handling and Storing:

USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY, AND OPEN FLAME.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Section XI - Regulatory Information

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Upper % Limit</u>
None.		

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2005. 2. OSHA PEL. 3. VENDOR'S MSDS. 4. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINPOweb, 2005. ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING. - IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE, COMB:COMBUSTIBLE, CORR:CORROSIVE CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED CUP, LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LIMIT, STEL:SHORT-TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE, MUT: MUTAGENIC, ASPHYX:ASPHYXIAN, PNOs:PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, SDT:STANDARD DRAIZE TEST, ORL:ORAL, IHL:INHALATION, HMN:HUMAN
THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2007 NCH Corporation All rights reserved.