

MATERIAL SAFETY DATA SHEET: QWIK-START AEROSOL

Section I - General Information

(000000-000000- - 5009)

Date of Issue:

10/4/2006 12:00:00 AM

Chemical Name & Synonyms:

N/A

Chemical Family:

ETHER/HYDROCARBON BLEND

Manufacturer Name:

CERTIFIED LABS, DIV. OF NCH CORP.

Manufacturer Address:

BOX 152170
IRVING, TEXAS 75015

Prepared By:

E Levi/Chemist

Supersedes:

6/18/2001 12:00:00 AM

Trade Name & Synonyms:

QWIK-START AEROSOL

Formula is a mixture: [V]

Product Code Number:

5009

Emergency Phone Number:

800-424-9300

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Chemical Name (Ingredients)	Hazard	TLV	PEL	STEL	CAS #
CARBON DIOXIDE	ASPHYXIANT	5000 PPM 1	5000 PPM 2	30000 PPM1	124-38-9
DIETHYL ETHER	IRR/FLAM	400 PPM 1	400 PPM 2	500 PPM 1	60-29-7
N-HEPTANE	IRR/FLAM	400 PPM 1	500 PPM 2	500 PPM 1	142-82-5
\$ SKIN VALUE					

Section III - Physical Data

Boiling Point (°F):94°	Specific Gravity (H ₂ O=1):0.70
Vapor Pressure (mm Hg):4137	Color:COLORLESS
Vapor Density (Air=1):2.5	Odor:ETHER
pH @ 100% :N/A	Clarity:TRANSPARENT
% Volatile by Volume:100	Evaporation Rate (BuAc=1):6
H ₂ O Solubility:EMULSIFIABLE	Viscosity:NON-VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point: <-56°F
Flammable Limits: PRODUCT MIXTURE
LEL: 1.0

Method Used: T.C.C.

UEL: 48.0

Aerosol Level (NFPA 308): 3

Extinguishing Media:

[] Foam [V] Alcohol Foam [V] CO2
[V] Dry Chemical [] Water Spray [V] Other

NFPA 704 Hazard Rating:

4-Extreme Health: 1
3-High Flammability: 4
2-Moderate Instability: 0
1-Slight Special:
0-Insignificant

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

PRODUCT MAY PRODUCE A FLOATING FIRE HAZARD AS LIQUID FLOATS ON WATER. THE USE OF WATER SPRAY (FOG) WHILE EFFECTIVE, MAY CAUSE FROTHING AND FOAMING. NEVER USE A WATER JET AS THIS WILL JUST SPREAD THE FIRE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO DISTANT AND/OR LOW-LYING SOURCES OF IGNITION AND FLASHBACK. FLAME EXTENSION IS 48 INCHES, BURNDACK IS 36 INCHES. USE CARE AS SPILLS MAY BE SLIPPERY.

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:

Acute: (Short Term Exposure)

EYE CONTACT: CAUSES IRRITATION SEEN AS REDNESS, STINGING, TEARING, AND SWELLING. PROLONGED CONTACT MAY CAUSE DAMAGE TO EYE TISSUE. SKIN CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS. PRODUCT MAY BE ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEFATTING, AND CRACKING, OF THE SKIN. INHALATION: MAY CAUSE RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. AT LOW VAPOR CONCENTRATIONS, NO HARMFUL EFFECTS ARE EXPECTED. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND MAY BE FATAL. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SIMILAR TO INHALATION. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL.

Chronic: (Long Term Exposure)

ACIDOSIS, ADRENAL CORTICAL EXHAUSTION, AND OTHER METABOLIC STRESSES HAVE RESULTED FROM PROLONGED CONTINUOUS EXPOSURE TO 1-2% CARBON DIOXIDE (10,000 PPM-20,000 PPM). MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS. TARGET ORGANS: CENTRAL NERVOUS SYSTEM. THE PRIMARY ROUTES OF EXPOSURE ARE SKIN AND EYE CONTACT.

Primary Routes of Entry

[V] Inhalation [] Ingestion [V] Absorption

Emergency First Aid Procedures:

Inhalation:

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

Eye Contact:

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

MATERIAL SAFETY DATA SHEET: QWIK-START AEROSOL

Skin Contact:

WASH AFFECTED AREAS WITH PLENTY OF SOAP AND WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Ingestion:

GIVE 3 TO 4 GLASSES OF WATER. BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. SEEK MEDICAL ATTENTION IF DISCOMFORT OCCURS.

Notes to Physician:

THERE IS NO SPECIFIC ANTIDOTE. TREAT THE PATIENT SYMPTOMATICALLY. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:

[] IARC [] NTP [] OSHA [] ACGIH [] Other

VOC CONTENT: 94.5% BY WEIGHT

CARBON DIOXIDE

IHL-RAT TCLO: 10000 PPM/24(S)-30 DAYS CONTINUOUS 4.

IHL-HMN LCLO: 9 PPM/5M 4.

IT HAS BEEN REPORTED THAT PERSONS MAY TOLERATE 1.5% IN INHALED AIR FOR PROLONGED PERIODS WITHOUT ADVERSE EFFECTS, BUT CALCIUM/PHOSPHORUS METABOLISM MAY BE AFFECTED WITH SERUM LEVELS OF CALCIUM AND URINARY PHOSPHORUS PROGRESSIVELY FALLING. AT 2% CONCENTRATION DEEPENED RESPIRATION MAY OCCUR. AT 3% IMPAIRMENT OF PERFORMANCE HAS BEEN NOTED. IT HAS, HOWEVER, BEEN DEMONSTRATED THAT THE DEVELOPMENT OF TOLERANCE MAY OCCUR DURING PROLONGED EXPOSURE TO LOW LEVELS. OXYGEN DEFICIENCY DURING PREGNANCY HAS PRODUCED DEVELOPMENTAL ABNORMALITIES IN HUMANS AND EXPERIMENTAL ANIMALS.

EXPOSURE OF FEMALE RATS TO 60,000 PPM CARBON DIOXIDE FOR 24 HOURS HAS PRODUCES TOXIC EFFECTS TO THE EMBRYO AND FETUS IN PREGNANT RATS. 4.

DIETHYL ETHER

ORL-RAT LD50: 1215 MG/KG 3.

N-HEPTANE

IHL-RAT LC50: 103 G/M3/4H 3.

ORL-RAT TDLO: 60 G/KG/3W-1 3.

Section VII - Reactivity Data

Stability

[V] Stable [] Unstable

Conditions to Avoid:

AVOID HEAT, HOT SURFACES, SPARKS, AND OPEN FLAMES. FORMS UNSTABLE PEROXIDES UPON PROLONGED CONTACT WITH AIR WHICH CAN CONCENTRATE AND EXPLODE UPON EVAPORATION.

Hazardous Polymerization

[V] Will not occur [] May occur

Conditions to Avoid:

N/A

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE.

Hazardous Decomposition Products:

OXIDES OF CARBON AND NITROGEN.

Section VIII - Spill Or Leak Procedures

Steps to be Taken if Material is Released or Spilled:

DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, WEAR APPROPRIATE PROTECTIVE CLOTHING, VENTILATE THE AREA, ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. USE CARE AS SPILLS MAY BE SLIPPERY.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. TYPICAL DISPOSAL IS TO WRAP THE EMPTY AEROSOL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN THE TRASH. AEROSOL RECYCLING PROGRAMS ARE AVAILABLE IN MANY AREAS. DO NOT PUNCTURE OR INCINERATE THIS CONTAINER.

Neutralizing Agent:

N/A

Section IX - Special Protection Information

Required Ventilation:

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF VAPORS OR MISTS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACESPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSI Z88.2-1992.

Glove Protection:

NEOPRENE OR NITRILE RUBBER GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:

SAFETY GLASSES WITH SIDE SHIELDS IF THE METHOD OF USE PRESENTS THE LIKELIHOOD OF EYE CONTACT. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:

WEAR GENERAL-DUTY WORK CLOTHES AND SHOES. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

Section X - Storage and Handling Information

Storage Temperature

Max: 100°F Min: 0°F

Storage Conditions

[V] Indoors [] Outdoors [] Heated [] Refrigerated

Precautions to be Taken in Handling and Storing:

MATERIAL SAFETY DATA SHEET: QWIK-START AEROSOL

USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY, AND OPEN FLAME.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Section XI - Regulatory Information

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Upper % Limit</u>
None.		

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2006.
2. OSHA PEL.
3. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFODisc, 2006.
4. VENDOR'S MSDS.

ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING.
IRR: IRRITANT, FLAM/FLAMM: FLAMMABLE, TOX: TOXIC, IHL: INHALATION, COMB: COMBUSTIBLE, CORR: CORROSIVE, CARC: CARCINOGENIC, N/A: NOT APPLICABLE, N/E: NOT ESTABLISHED, COC: CLEVELAND OPEN CUP, PMCC: PENSKEY-MARTIN CLOSED CUP, TCC: TAGLIABUE CLOSED CUP, LEL: LOWER EXPLOSION LIMIT, UEL: UPPER EXPLOSION LIMIT, HMN: HUMAN, IARC: INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NFPA: NATIONAL FIRE PROTECTION ASSOCIATION, ORL: ORAL, NTP: NATIONAL TOXICOLOGY PROGRAM, OSHA: OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV: THRESHOLD LIMIT VALUE, PEL: PERMISSIBLE EXPOSURE LIMIT, STEL: SHORT-TERM EXPOSURE LIMIT, MLD: MILD, MOD: MODERATE, SEV: SEVERE, MUT: MUTAGENIC, ASPHYX: ASPHYXIANT, PNOC: PARTICULATES NOT OTHERWISE CLASSIFIED, PNOR: PARTICULATES NOT OTHERWISE REGULATED, PNOS: PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, SDT: STANDARD DRAIZE TEST
THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2007 NCH Corporation All rights reserved.