

PARIS PAINT & VARNISH CO., INC
965 STANLEY AVENUE
BROOKLYN, NEW YORK U.S.A. 11208
718-272-7550

PRODUCT : NY4019 PARIS SUPER DELUXE ALKYD BLACK

SECTION 01 : PRODUCT IDENTIFICATION

MANUFACTURER.....PARIS PAINT & VARNISH CO., INC
965 STANLEY AVENUE
BROOKLYN, NEW YORK
U.S.A. ; 11208
718-272-7550
1-800-272-7471

PRODUCT IDENTIFICATION.....NY4019 PARIS SUPER DELUXE ALKYD BLACK

PRODUCT USES.....COATING

CHEMICAL FAMILY.....ALKYD PAINT.

MATERIAL USE.....HOUSE PAINT

SECTION 02 : HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	T.L.V.	C.A.S. #	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
MINERAL SPIRITS	30-60	200ppm 200ppm	64742-47-8	ORALE >5000 MG/KG (RAT) DERMAL >2000 MG/KG (RABBIT)	3400 PPM 4 HOURS RAT
XYLENE	.5-1.5	100 ppm/435 mg/m3 100 ppm/435 mg/m3	1330-20-7	ORAL(RAT):4300 mg/kg DERM(RBT):2000 mg/kg	5000 ppm 4 HOURS RAT INHALATION

SECTION 03 : HAZARDS IDENTIFICATION

ROUTE OF ENTRY

SKIN CONTACT.....SLIGHT IRRITATION

SKIN ABSORPTION.....REPEATED CONTACT MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS

INHALATION.....INHALATION OF VAPOURS OR SANDING DUSTS MAY CAUSE IRRITATION OF THE
RESPIRATORY OR MUCOSAL MEMBRANES. BREATHING OF HIGH VAPOUR CONCENTRATIONS
MAY HAVE RESULTS RANGING FROM DIZZINESS AND HEADACHE TO UNCONSCIOUSNESS.

INGESTION.....MAY BE HARMFUL OR FATAL IF SWALLOWED

EYE CONTACT.....CONTAINS MATERIALS THAT ARE MODERATELY IRRITATING TO THE EYES

EFFECTS OF ACUTE EXPOSURE.....MAY CAUSE NAUSEA, DIZZINESS, HEADACHE FROM INHALATION OF VAPOR. SKIN CONTACT
MAY CAUSE IRRITATION. ALLERGIC REACTIONS MAY RESULT IN SOME CASES.

SECTION 04 : FIRST AID MEASURES

EYE CONTACT.....IMMEDIATELY FLUSH WITH WATER FOR A MINIMUM OF 20 MINUTES. GET MEDICAL
ATTENTION.

SKIN CONTACT.....REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH WATER AND SOAP.
SEEK MEDICAL ATTENTION IF IRRITATION OCCURS OR PERSISTS.

INHALATION.....REMOVE VICTIM TO FRESH AIR. IF NOT BREATHING QUALIFIED PERSONNEL SHOULD
ADMINISTER ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.

INGESTION.....DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

ADDITIONAL INFORMATION.....TREATMENT OF OVER EXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS
& THE CLINICAL CONDITION.

SECTION 05 : FIRE FIGHTING MEASURES

FLAMMABILITY.....YES

IF YES, UNDER WHICH.....SPARKS, OPEN FLAMES AND ALL OTHER SOURCES OF IGNITION. AT ELEVATED
CONDITIONS? TEMPS. VAPOUR MAY FORM EXPLOSIVE MIXTURE WITH AIR.

FLASH POINT (C), METHOD.....56 C (T.C.C.)

AUTO IGNITION TEMPERATURE.....NOT AVAILABLE

UPPER FLAMMABLE LIMIT (% VOL).....NOT AVAILABLE

LOWER FLAMMABLE LIMIT (% VOL).....NOT AVAILABLE

EXTINGUISHING MEDIA.....CARBON DIOXIDE, DRY CHEMICAL, FOAM

HAZARDOUS COMBUSTION PRODUCTS.....NOT AVAILABLE

SENSITIVITY TO MECHANICAL.....NONE

IMPACT

SENSITIVITY TO STATIC.....NOT AVAILABLE

DISCHARGE

PRODUCT : NY4019 PARIS SUPER DELUXE ALKYD BLACK

SECTION 06 : ACCIDENTAL RELEASE MEASURES

LEAK/SPILL.....REMOVE SOURCES OF FIRE, ENSURE ADEQUATE VENTILATION. KEEP UNAUTHORIZED PERSONS AWAY. REMOVE MECHANICALLY; COVER REMAINDERS WITH WET, ABSORBENT MATERIAL (e.g. SAND, SAWDUST, CALCIUM SILICATE HYDRATE). AFTER ONE HOUR TRANSFER TO WASTE CONTAINER AND DO NOT SEAL (EVOLUTION OF CO₂). KEEP DAMP IN A SAFE AREA FOR SEVERAL DAYS.

SECTION 07 : HANDLING AND STORAGE

HANDLING PROCEDURES.....AVOID BREATHING VAPORS. AVOID SMOKING WHEN MATERIAL IS USED. AVOID SHOCK AND FRICTION. USE NON-METALLIC TOOLS.
STORAGE NEEDS.....KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. STORE IN A COOL AND WELL-VENTILATED AREA.

SECTION 08 : EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

EYE/TYPE.....GOGGLES
RESPIRATORY/TYPE.....APPROVED AIR PURIFYING RESPIRATOR FOR DUST AND VAPOR OR AIR SUPPLIED.
GLOVES/ TYPE.....CHEMICAL RESISTANT GLOVES.
CLOTHING/TYPE.....CHEMICAL RESISTANT
FOOTWEAR/TYPE.....SAFETY BOOTS PER LOCAL REGULATIONS

SECTION 09 : PHYSICAL PROPERTIES

PHYSICAL STATE.....LIQUID
ODOR.....SOLVENT LOW ODOUR
SPECIFIC GRAVITY.....1.1684
ODOR THRESHOLD (ppm).....NOT APPLICABLE
VAPOR PRESSURE (mm Hg).....NOT AVAILABLE
VAPOUR DENSITY (AIR=1).....NOT AVAILABLE
EVAPORATION RATE.....NOT AVAILABLE
BOILING POINT (deg C).....NOT AVAILABLE
PH.....NOT APPLICABLE
SOLUBILITY IN WATER (% W/W).....INSOLUBLE
COEFFICIENT OF WATER/OIL.....NOT APPLICABLE
DISTRIBUTION
FREEZING POINT.....NOT APPLICABLE
MELTING POINT (deg C).....NOT AVAILABLE
VOLATILE %.....30-35

SECTION 10 : STABILITY AND REACTIVITY

STABILITY.....YES
REACTIVITY CONDITIONS.....IN THE PRESENCE OF OXIDIZING MATERIALS
HAZARDOUS PRODUCTS OF.....COMBUSTION PRODUCTS INCLUDE WATER, CARBON DIOXIDE & CARBON MONOXIDE
DECOMPOSITION

SECTION 11 : TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL.....SEE HAZARDOUS INGREDIENTS SECTION (2)
IRRITANCY OF MATERIAL.....NOT APPLICABLE
SENSITIZING CAPABILITY OF.....NOT AVAILABLE
MATERIAL
SYNERGISTIC MATERIALS.....NOT APPLICABLE.

SECTION 12 : ECOLOGICAL INFORMATION

ENVIRONMENTAL.....NOT AVAILABLE
BIODEGRADABILITY

SECTION 13 : DISPOSAL CONSIDERATIONS

WASTE DISPOSAL.....IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS.

SECTION 14 : TRANSPORT INFORMATION

T.D.G. CLASSIFICATION.....PAINT RELATED MATERIALS UN:1263 CLASS:3 GROUP III

PRODUCT : NY4019 PARIS SUPER DELUXE ALKYD BLACK

SECTION 15 : REGULATORY INFORMATION

WHMIS CLASSIFICATION.....CATEGORY B.DIVISION 3 ; CATEGORY D. DIVISION 2. SUBDIVISION A ; CATEGORY D
DIVISION 2. SUBDIVISION B

SECTION 16 : OTHER INFORMATION

NOTE:.....THE ADDITION OF COLORANTS, AFTER MANUFACTURE, MAY ADD 0.1 - 0.4% OF
ETHYLENE GLYCOL (CAS # 107-21-1) EXPOSUREE LIMIT TLV 50 ppm AND OTHER
HAZARDOUS INGREDIENTS.
DATED.....JUL 06/04